

date of issue : 07/04/2014

Safety Data Sheets

1. Product and Company Identification

Product name :Kiwami Putty 80

Name of supplier :SOLAR CO., LTD.

Address :1-7, Nunobiki-cho-2-chome, Chuo-ku, Kobe, Hyogo-Pref. 651-0097 JAPAN

Division :R & D DEPT.

Phone :+81-790-49-2366

FAX :+81-790-49-1588

Product code(SDS NO) :EN400911-6

2. Hazards identification

GHS classification and label elements of the product

GHS classification

PHYSICAL HAZARDS

Flammable solid : Category 1

HEALTH HAZARDS

Skin corrosion/irritation : Category 2

Eye damage /eye irritation : Category 2

Germ cell mutagenicity : Category 2

Reproductive toxicity : Category 1B

Specific target organ toxicity-single exposure : Category 1

Specific target organ toxicity - single exposure; Respiratory tract irritation Category 3

Specific target organ toxicity-repeated exposure : Category 1

ENVIRONMENT HAZARDS

Hazardous to the aquatic environment-acute toxicity : Category 3



Signal word : Danger

HAZARD STATEMENT

Flammable solid

Causes skin irritation.

Causes eye irritation

Suspected of causing genetic defects

May damage fertility or the unborn child

Causes damage to organs after single exposure.

May cause respiratory irritation

Causes damage to organs following repeated exposure.

Harmful to aquatic life

PRECAUTIONARY STATEMENT

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash contaminated parts thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Avoid release to the environment.

Wear protective gloves/eye protection/face protection.

Use personal protective equipment as required.

Response

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash before reuse.

IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use appropriate media other than water for extinction.

Storage

Store locked up.

Store in well-ventilated place. Keep container tightly closed.

Disposal

Dispose of contents/container in accordance with local/national regulation.

3. Composition/Information on Ingredients

Substance/Preparation :Preparation

Ingredient name	content(%)	CAS No.	PRTR law No, Japan
Unsaturated polyester resin	20 - 25	Non Public	-
Styrene	20	100-42-5	1-240
Cobalt naphthenate	<1.0	61789-51-3	1-132
Cobalt 2-ethylhexanoate		136-52-7	1-132
Amorphous silica	0.1 - 1	7631-86-9	-
Extender · Hollow powder	50 - 55	Non Public	-
Additive	1 - 5	Non Public	-

4. First-aid measures

IF INHALED

Remove victim to fresh air and keep at rest in a position comfortable for breathing.

If experiencing respiratory symptoms call a POISON CENTER or doctor/physician.

IF ON SKIN(or hair)

Never use solvent or thinner.

Wash with plenty of soap and water.

If you observe unusual symptom, have irritation/pain and/or feel unwell, seek medical advice.

IF IN EYES :

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF SWALLOWED

Rinse mouth.

Do NOT induce vomiting.

Immediately call a POISON CENTER or doctor/physician.

5. Fire-fighting measures

Suitable extinguishing media

In case of fire, use water mist, foam, dry powder or CO2.

Specific fire-fighting measures

Use appointed fire extinguisher.

Remove flammable matters quickly from nearby.
Apply water from a safe distance to cool and protect surrounding area.
Special protective equipment and precautions for fire-fighters
Fire extinguishing work has to be done from windward.
Wear proper protective equipment.

6. Accidental Release Measures

Personnel precautions, protective equipment and emergency procedures
Ventilate area after material pick up is complete.
Wear proper protective equipment.
Keep unauthorized personnel away.
Environmental precautions
Prevent spills from entering sewers, watercourses or low areas.
Methods and materials for neutralization, containment and cleaning up
Place in a covered container.
Use non-sparking tools to collect absorbed material.
Preventive measures for secondary accident
Prepare extinguishers before catching fire.

7. Handling and Storage

Precautions for safe handling
Preventive measures
Use personal protective equipment as required.
Take precautionary measures against static discharge.
Safety treatments
Used waste or spray-dust has to be dipped in water until disposition.
Safety Measures/Incompatibility
Handle in good ventilation.
Do not handle until all safety precautions have been read and understood.
Conditions for safe storage, including any incompatibilities
Recommendation for storage
Keep container tightly closed.
Protect from sunlight. Store in a well-ventilated place.

8. Exposure Controls/Personal Protection

Control parameters e.g. occupational exposure limit values or biological limit values
Control value
(Styrene)
Japan control value (2004) \leq 20ppm
Adopted value
(Styrene)
JSOH(1999) 20ppm; 85mg/m³ (dermal)
(Cobalt 2-ethylhexanoate)
JSOH(1992) 0.05mg-Co/m³
(Cobalt naphthenate)
JSOH(1992) 0.05mg-Co/m³
(Styrene)
ACGIH(1996) TWA: 20ppm
STEL: 40ppm (CNS impair; URT irr; periph neuropathy)
Appropriate engineering controls
Do not use in areas without adequate ventilation.
Exhaust/ventilator should be available.
Protective equipment
Respiratory protection

- Wear respiratory protection.
 - Hand protection
 - Wear protective gloves.
 - Eye protection
 - Wear eye/face protection.
 - Skin and body protection
 - Wear protective gloves/clothing
-

9. Physical and Chemical Properties

Physical properties

- Appearance :paste
 - Color :gray
 - Flash point :31 (Closed style) (ref.value/Styrene)
 - Specific gravity :ca 1.28
-

10. Stability and Reactivity

Stability

- Stable under normal storage/handling conditions.
-

11. Toxicological Information

Symptoms related to the physical, chemical and toxicological characteristics

Acute toxicity

Oral toxicity component(s) data

- (Styrene)
 - rat LD50=5000 mg/kg (CERI_NITE hazard assessment data No.52, 2004)
- (Cobalt naphthenate)
 - rat LD50=3900 mg/kg (JPMA 5th ed.)

Inhalation toxicity component(s) data

- (Styrene)
 - vapor : rat LC50 = 2770 ppm/4hr (cal.)

Irritant properties

Skin corrosion/Irritation component(s) data

- (Styrene)
 - rabbit 500 mg open ; MILD

Mutagenic effects

- (Styrene) ACGIH, 2001

Carcinogenic effects

- (Styrene)
 - IARC-Gr.2B ; Possibly carcinogenic to humans.
- (Amorphous silica)
 - IARC-Gr.3 ; Not Classifiable as a Human Carcinogen.
- (Styrene)
 - ACGIH-A4(1996) : Not Classifiable as a Human Carcinogen
- (Styrene)
 - JSOH-2B; Insufficient Evidence of Carcinogenicity for Humans

Toxicity for reproduction

- (Styrene) CERI/NITE hazard assessment No.52, 2004

Delayed and immediate effects and also chronic effects from short- and long-term exposure

Specific target organ toxicity (single exposure cat.1)

- (Styrene) CNS (EHC 26, 1983)

Specific target organ toxicity (single exposure cat.3 respiratory irritation)

- (Styrene) Respiratory tract irritation (EHC 26, 1983)

Specific target organ toxicity (repeated exposure cat.1)

- (Styrene) respiratory apparatus/system; nerve/nervous system; blood/blood system; liver (

CERI/NITE hazard assessment, 2004)

Aspiration hazard

(Styrene) hydrocarbon, kinematic viscosity =0.772 mm²/s (25)

12. Ecological Information

Ecotoxicity

Aquatic toxicity

Harmful to aquatic life

(Styrene)

Fish (fat head minnow) LC50=4.02 mg/L/96hr (CERI/NITE, 2004)

Water solubility

(Styrene)

0.03 g/100 ml (20 C) (ICSC, 2006)

(Cobalt naphthenate)

none (ICSC, 2000)

Persistence and degradability

(Styrene)

BOD_Degradation : 100% (Registered chemicals data check & review, Japan)

Bioaccumulative potential

(Styrene)

log Kow=2.95 (PHYSPROP Database, 2005)

13. Disposal Considerations

Disposal methods

Avoid release to the environment (- if this is not the intended use).

Dispose of contents/container in accordance with local/national regulation.

14. Transport Information

UN No, UN CLASS

UN No :1325

UN CLASS :4.1

PG :III

Proper shipping name :FLAMMABLE SOLID, ORGANIC, N.O.S.

ERG GUIDE NO :133

Ship cargo control law, Japan

Flammable solids, self-reactive substances and solid desensitised explosives

Air cargo control law, Japan

Flammable solids, self-reactive substances and solid desensitised explosives

Special precautions in connection with transport or conveyance

Follow instruction in Handling & Storage.

15. Regulatory Information

Industrial Safety and Health law, Japan

Organic Solvents Class II :Styrene

Harmful substances to be indicated :Styrene

Chemical name et al should be informed :Styrene

Cobalt 2-ethylhexanoate;Cobalt naphthenate;Amorphous silica

PRTR law, Japan

Listed chemicals Gr.1 :Styrene

Fire protection law, Japan

Flammable solids : flammable solids (Class III)

Chemical Substances Control Law, Japan

Priority Assessment Chemical Substances :Styrene

16. Other information

Reference Book

Globally Harmonized System of classification and labelling of chemicals, (4th ed., 2011), UN
Recommendations on the TRANSPORT OF DANGEROUS GOODS 17th edit. UN

2012 EMERGENCY RESPONSE GUIDEBOOK(US DOT)

2011 TLVs and BEIs. (ACGIH)

<http://monographs.iarc.fr/monoeval/grlist.html>

Supplier's data/information

Other information

This information contained in this data sheet represents the best information currently available to us. However, no warranty is made with respect to its completeness and we assume no liability resulting from its use. It are advised to make their own test